

# Feusilit FSK

Fire-retarding sealing made of special mortar for feedthrough of fire dampers in massive walls and floors.



Label

PYRO-SAFE NOVASIT K2 /  
PYRO-SAFE NOVASIT VGM  
Fire protection mortar

Fire damper

Subject to errors, typographical errors and modifications. The specified details reflect the state of the art / the effective standard at the time of printing (09/2014). Please let us know when you need information about the legal and technical requirements or the manufacturer's specification that apply to your specific case. © Copyright svt Unternehmensgruppe, Seevetal. PYRO-SAFE is a registered trademark © of svt Unternehmensgruppe, Seevetal.

## System description

### Applications

Fire-retarding sealing made of special mortar for feedthrough of ventilation ducts in massive walls and floors.

### Characteristics

Easy to handle, fire resistant and smoke tight, temperature reducing, resistant against hose stream pressure, mechanically stable.

### Fire protection features

Supports up to 4 hours integrity and insulation according to the approvals of fire damper systems

### Applicability certificate

Tested and approved according to national and international standards as e.g.:  
DIN 4102,  
other standards on request

Joins

## Technical Data

---

### Particular points to note

Installation and handling permitted only in accordance with the manufacturer's approval and mounting Instruction.

### Preliminary building work

None required in massive walls and floors. Dimension of the surrounding joint according to the manufacturer's approval of the fire dampers.

## Components

---

- PYRO-SAFE NOVASIT K2/PYRO-SAFE NOVASIT VGM Fire protection mortar
- Label